

Microphone preamplifier for high sound level measurements

MP802

Introduzione

High sound level measurements demand a microphone chain that can handle intense acoustic pressure without losing traceability in the instrument setup. MP802 is the preamplifier used with the MC802 ¼" pressure measurement microphone in the MS802 microphone set, extending XPT800-H and XPT801-H configurations up to 178 dBpeak.

The preamplifier supports Sensor Digital Interface, allowing the sound level meter to work with automatic model identification and calibration data handling. Together with the MC802 microphone, it forms a compact ¼" pressure microphone chain for applications where standard ½" microphone sets reach their upper limit.

For acoustic professionals working in industrial noise, product testing or other high-level acoustic tasks, MP802 adds range flexibility while keeping the measurement chain aligned with the XPT800 and XPT801 platform. The associated MC802 microphone is specified to IEC 61094-4 WS4P, with 0.56 mV/Pa sensitivity and a 10 Hz–20 kHz frequency range.



High-level range

Enables MS802 dynamic range from 65 dBA to 178 dBpeak with MC802.



XPT compatibility

Used in XPT800-H and XPT801-H high sound level configurations.



Smart identification

Sensor Digital Interface supports automatic model and calibration data handling.



¼" microphone chain

Works with MC802 pressure microphone for compact high-level acoustic measurement.



Visualizza il prodotto sul nostro sito

prod.senseca.apprunner.info/it/prodotto/mp802-mp802

Caratteristiche

Sensor Digital Interface

MP802 includes SDI for communication with compatible XPT sound level meters, supporting instrument recognition of the connected microphone chain.

MC802 microphone pairing

The preamplifier is specified for use with the MC802 ¼" pressure measurement microphone with a 0.56 mV/Pa sensitivity. The mechanical adaptor MP80-MA is included, allowing 1/4" microphones to be connected to the 1/2" threaded connector.

High sound level configuration

In the MS802 microphone set, the MP802 and MC802 combination provides a dynamic range from 65 dBA to 178 dBpeak.

XPT-H instrument sets

MP802 is included in XPT800-H and XPT801-H configurations for high sound level measurements.

Frequency range

With the MC802 microphone, the microphone set covers 10 Hz–20 kHz for pressure measurement applications.