

Steel pins for moisture measurement

GST

Introduction

Practical moisture measurement often depends on the right contact accessory. This steel pin family gives users a choice of pin lengths, diameters and pack sizes for adapting the measurement setup to the material and handling situation.

The range includes steel pins with 2.5 mm diameter in lengths from 16 to 60 mm, plus drilled 3.8 mm variants in 15, 25 and 40 mm lengths. Users can select small sets in a plastic box, loose pins in plastic bags, larger 500-piece packs or Teflon-insulated pins for supported moisture measurement tasks.

Features

Steel pin variants

The family includes steel pins for use as accessories in moisture measurement.

Length options

Variants cover 16, 23, 30, 40, 45 and 60 mm lengths, depending on pin type and pack.

Diameter options

Standard variants use 2.5 mm diameter; drilled steel pin variants use 3.8 mm diameter.

Packaging formats

Selected variants are supplied loose in a plastic bag or packed in a plastic box.

Insulated pins

The range includes Teflon-insulated steel pins in 45 mm and 60 mm lengths.

Drilled pins

Drilled steel pins are available in 15 mm, 25 mm and 40 mm lengths.



Flexible selection

Choose 16, 23, 30, 40, 45 or 60 mm steel pins for moisture measurement accessories.



Two diameters

The range includes 2.5 mm pins and drilled 3.8 mm pins for different measurement setups.



Practical pack sizes

Available as 2-piece, 9-piece, 10-piece or 500-piece packs, depending on the variant.



Special variants

Teflon-insulated pins and drilled steel pins extend the accessory choice.

Technical Specifications

Probe

Probe Diameter	2.5 mm
Probe length	23 mm / 30 mm / 40 mm / 45 mm / 60 mm (depending on article)
Material	Steel / Teflon-insulated steel (depending on article)

Available standard product variants

Ordercode	Description	Article No.
GST91/23	GST91/23: 23 mm, Ø 2,5 mm, 10 pcs - Steel pins for moisture measurement, available in 16, 23, 30, 40, 45 and 60 mm lengths with 2.5 mm or 3.8 mm diameter, including loose, boxed, Teflon-insulated and drilled variants.	482936
GST91/30	GST91/30: 30 mm, Ø 2,5 mm, 10 pcs - Steel pins for moisture measurement, available in 16, 23, 30, 40, 45 and 60 mm lengths with 2.5 mm or 3.8 mm diameter, including loose, boxed, Teflon-insulated and drilled variants.	487640
GST91	GST91: Mixed - Steel pins for moisture measurement, available in 16, 23, 30, 40, 45 and 60 mm lengths with 2.5 mm or 3.8 mm diameter, including loose, boxed, Teflon-insulated and drilled variants.	601273
GST91/40	GST91/40: 40 mm, Ø 2,5 mm, 10 pcs - Steel pins for moisture measurement, available in 16, 23, 30, 40, 45 and 60 mm lengths with 2.5 mm or 3.8 mm diameter, including loose, boxed, Teflon-insulated and drilled variants.	601275
GST45I	GST45I: Teflon-insulated, 45 mm, Ø 2,5 mm, 2 pcs - Steel pins for moisture measurement, available in 16, 23, 30, 40, 45 and 60 mm lengths with 2.5 mm or 3.8 mm diameter, including loose, boxed, Teflon-insulated and drilled variants.	601277
GST60I	GST60I: Teflon-insulated, 60 mm, Ø 2,5 mm, 2 pcs - Steel pins for moisture measurement, available in 16, 23, 30, 40, 45 and 60 mm lengths with 2.5 mm or 3.8 mm diameter, including loose, boxed, Teflon-insulated and drilled variants.	601279