

Temperature

Spare Parts & Accessories: Cables

PVC

P2P

PVC cable, 2-wire

Cross-section: 2 x 0,14 mm²

Max. Temperature: -20 ... +70 °C

P4P

PVC cable, 4-wire

Cross-section: 4 x 0,14 mm²

Max. Temperature: -20 ... +70 °C

SILICONE

S2P

Silicone cable, 2-wire

Cross-section: 2 x 0,25 mm²

Max. Temperature: -50 ... +200 °C

S4P

Silicone cable, 4-wire

Cross-section: 4 x 0,14 mm²

Max. Temperature: -50 ... +200 °C

PTFE

T2P

Teflon cable, 2-wire

Cross-section: 2 x 0,14 mm²

Max. Temperature: -200 ... +250 °C

T4P

Teflon cable, 4-wire

Cross-section: 4 x 0,14 mm²

Max. Temperature: -200 ... +250 °C

GLASS-FIBER INSULATED WITH STAINLESS STEEL BRAIDING

G4P

Glass-silk-insulated cable, 4-wire

Cross-section: 4 x 0,22 mm²

Max. Temperature: -50 ... +400 °C

For every cable, length is specified as a three-digit number in the order code, e.g. P2P-L001: 1 m PVC cable, 2-wire