

CO-TRANSDUCER



WITH TÜV CERTIFICATE ACC.
TO VDI 2053 FOR
CO SURVEILLANCE SYSTEMS
IN UNDERGROUND
GARAGES ETC.

GT1-CO

Product-ID: 602858
CO-Transducer

General:

High quality, TÜV certified CO transmitter for detection of carbon monoxide in underground garages, parking garages, boiler plants, heating systems, garages as well as in the ambient air. The CO transducer has a very long-lasting electrochemical measuring cell and could be easily integrated in existing CO surveillance systems (without loss of validity of existing TÜV certificates). Via two-wire system, displays, controller and alarm devices with 4-20 mA input could be connected without any problem.

Highlights:

- TÜV certification according to VDI 2053
- also suitable as replacement sensor for existing CO surveillance systems
- long-lasting electrochemical measuring cell
- automatic zero calibration
- 3 years warranty for the CO sensor element

Application:

- underground garages, parking garages
- boiler plant and heating systems
- motorcar garage

Specifications:

Measuring range:	0 ... 300 ppm CO (carbon monoxide)
Measuring principle:	electrochemical, permanent measuring
Reproducibility:	< 3 ppm according to VDI 2053
Response Time T_{90}:	< 60 s
Cross sensitivity:	$\leq 2\%$ of 300 ppm CO (acc. to VDI 2053)
Linearity error:	$\leq 2\%$ of 300 ppm CO (acc. to VDI 2053)
Offset adjustment:	automatically
Output signal:	4 - 20 mA, 2 wire, max. burden = 500 Ohm
Power supply:	12 - 28 V DC (at option VO: 16 - 28 V DC)
Permissible burden:	$R_A [\Omega] \leq (U_v [V] - 12 V \text{ or } 16 V) / 0.02 A$
Working condition:	-10 ... +40 °C, 15 ... 95 % RH (non-condensing)
Option: on site display	approx. 13 mm high, 3½-digit LC-display
EMC:	according to EN 50 081-1, EN 50 082-2 B
Electric connection:	elbow-type plug acc. to EN 175301-803/A (IP65), max. wire cross section: 1.5 mm ² , wire diameter from 4.5 ... 7 mm
Housing:	ABS, 82 x 80 x 55 mm (without elbow-type plug)
Mounting:	with fixing holes for wall mounting
Mounting distance:	70 x 50 mm (W x H)
Fixing screws:	max. shaft-Ø 4 mm
Weight:	approx. 190 g

Variante:

GT1 - CO VO

Product-ID: 607965
CO Transducer with on site display

Accessories and spare parts:

GZ-01

Product-ID: 603122
test gas cap GT (for controlled flow with test gas)

GZ-02

Product-ID: 603569
gas bottle with 12l test gas: 30 ppm CO

GZ-03

Product-ID: 603123
gas bottle with 12l test gas: 300 ppm CO

GZ-04

Product-ID: 603570
gas valve unit MiniFlo for gas bottles with 12l

GSN-24

Product-ID: 604386
plug-in power supply (230 V_{AC} => 24 V_{DC}/300 mA)

CO₂-TRANSDUCER



GT10-CO2-1R

Product-ID: 602599
CO₂-Transducer

General:

Due to the fact, that CO₂ is an important indicator for the quality of air in rooms, it's super important to measure the CO₂ content. The recommended CO₂ limit value for ambient air is 1000 ppm. An exceeding of this limit causes tiredness and a loss of concentration. The high quality and precise CO₂-transducer works according to the infrared principle (NDIR). An auto-calibration procedure compensates aging effects and is responsible for an excellent long term stability of this CO₂ transducer. Due to the freely adjustable output signal the transmitter could be used for nearly each existing controller input etc. Additionally, there is a local display which shows beside the actual CO₂ concentration, the minimum and maximum values as well as an optical alarm.

Highlights:

- excellent long term stability
- auto-calibration procedure
- for surveillance of the recommended CO₂ concentration in ambient air
- output signal free scaleable

Specifications:

Measuring range:	standard: 0 ... 2000 ppm CO ₂ (carbon dioxide) optional: 0 ... 5000 ppm CO ₂ (carbon dioxide)
Measuring principle:	infrared principle (NDIR)
Accuracy:	standard: ± 50 ppm $\pm 2\%$ of meas. value (at 20 °C, 1023 mbar) opt. /5000: ± 50 ppm $\pm 3\%$ of meas. value (at 20 °C, 1023 mbar)
Output signal:	4 - 20 mA (3-wire), standard 0 - 1 V or 0 - 10 V (3-wire), upon upcharge
Output scaling:	free scaleable, by entering display range
Auxiliary energy:	12 ... 30 V DC, max. 600 mA (at option 0-10 V: 18 ... 30 V DC, max. 600 mA)
Permissible burden (at 4-20 mA):	$R_A < 200 \Omega$
Perm. load (at 0...Volt):	$R_L > 3000 \Omega$
Display:	approx. 10 mm high, 4-digit LC-display
Working condition:	-10 ... +50 °C, 5 ... 95 % RH, 850 ... 1100 hPa
Storage condition:	-25 ... +60 °C, 5 ... 95 % RH, 700 ... 1100 hPa
Electric connection:	elbow-type plug acc. to EN 175301-803/A (IP65), max. wire cross section: 1.5 mm ² , wire diameter from 4.5 ... 7 mm
Housing:	ABS, 82 x 80 x 55 mm (without elbow-type plug)
Mounting:	with fixing holes for wall mounting
Mounting distance:	70 x 50 mm (W x H)
Fixing screws:	max. shaft-Ø 4 mm
Weight:	approx. 225 g
Features:	- min-/max-value memory, - optical alarm, - input of offset and scale for adjusting

Option:

MB2:

measuring range: 0 ... 5000 ppm CO₂

AV01:

output signal 0 - 1 V

AV010:

output signal 0 - 10 V

Accessories and spare parts:

GSN 24-750

Product-ID: 604387
plug-in power supply (230 V_{AC} => 24 V_{DC}/750 mA)